

3406C
350 ekW/ 438 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor

Rating Type: **STANDBY**

Fuel Strategy: **LOW FUEL CONSUMPTION**

3406C
350 ekW/ 438 kVA
60 Hz/ 1800 rpm/ 480 V



Image shown may not reflect actual configuration

Metric

English

Package Performance

Genset Power Rating with Fan @ 0.8 Power Factor	350 ekW	
Genset Power Rating	438 kVA	
Aftercooler (Separate Circuit)	78.0 ° C	172.4 ° F

Fuel Consumption

100% Load with Fan	100.5 L/hr	26.5 gal/hr
75% Load with Fan	75.7 L/hr	20.0 gal/hr
50% Load with Fan	53.7 L/hr	14.2 gal/hr
25% Load with Fan	32.9 L/hr	8.7 gal/hr

Cooling System¹

Engine Coolant Capacity	N/A	N/A
-------------------------	-----	-----

Inlet Air

Combustion Air Inlet Flow Rate	26.6 m³/min	940.4 cfm
Max. Allowable Combustion Air Inlet Temp	90 ° C	194 ° F

Exhaust System

Exhaust Stack Gas Temperature	551.1 ° C	1023.9 ° F
Exhaust Gas Flow Rate	76.6 m³/min	2704.1 cfm
Exhaust System Backpressure (Maximum Allowable)	6.7 kPa	27.0 in. water

3406C
350 ekW/ 438 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor

Rating Type: STANDBY

Fuel Strategy: LOW FUEL CONSUMPTION

Heat Rejection

Heat Rejection to Jacket Water	229 kW	13024 Btu/min
Heat Rejection to Exhaust (Total)	374 kW	21271 Btu/min
Heat Rejection to Aftercooler	37 kW	2110 Btu/min
Heat Rejection to Atmosphere from Engine	83 kW	4744 Btu/min
Heat Rejection to Atmosphere from Generator	21 kW	1206 Btu/min

Alternator²

Motor Starting Capability @ 30% Voltage Dip	1309 skVA
Current	527 amps
Frame Size	LC6124D
Excitation	AR
Temperature Rise	105 ° C

Emissions (Nominal)³

NOx	3111.2 mg/Nm ³	6.7 g/hp-hr
CO	1801.3 mg/Nm ³	4.1 g/hp-hr
HC	23.4 mg/Nm ³	0.1 g/hp-hr
PM	414.4 mg/Nm ³	1.2 g/hp-hr

DEFINITIONS AND CONDITIONS

1. For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.
2. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40° C ambient per NEMA MG1-32.
3. Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

3406C

350 ekW/ 438 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor

Rating Type: STANDBY

Fuel Strategy: LOW FUEL CONSUMPTION

Applicable Codes and Standards:

AS1359, CSA C22.2 No100-04, UL142, UL489, UL869, UL2200,
NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC60034-1, ISO3046, ISO8528,
NEMA MG1-22, NEMA MG1-33, 2006/95/EC, 2006/42/EC, 2004/108/EC.

Note: Codes may not be available in all model configurations. Please consult your local Cat Dealer representative for availability.

STANDBY: Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

Fuel Rates are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

www.Cat-ElectricPower.com

Performance No.: DM2271-03

Feature Code: 406DER9

Generator Arrangement: 2351208

Date: 03/06/2016

Source Country: U.S.

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.