Waukesha\*gas engines

# **APG1000**

APG\* Gas Enginator\* Generating System 1000 kWe @ 50 Hz/1100 kWe @ 60 Hz

### CHP

The APG1000 Combined Heat and Power (CHP) package allows for optimized efficiency by maximizing heat recovery. This minimizes packaging cost and time by including CHP components factory mounted. Achieve up to **89.4%** total efficiency with the APG1000 CHP package.

With a reputation for rugged durability and ongoing design advancements, Waukesha engines are the sound investment you can depend on in mission-critical applications. Now a part of GE Power & Water, Waukesha provides enhanced support in the form of parts, service and a network of distributors to make us an even stronger partner for today's global energy industry.

### reference installations

key technical data

#### model, site

#### APG1000 Sicily, Italy

Fuel Na

Fuel	Natural gas
Engine type	APG1000
Electrical output	1000 kWe
Thermal output	1100 kW
Commissioning	1st Quarter 2012

### description

A Hospital in Catania, Sicily, Italy is installing the Waukesha APG1000 CHP package. Hospitals have a high heat load making CHP a perfect fit to maximize energy efficiency and cost savings.



#### APG1000 Seika Teisyo, China

Fuel	Sewage gas (WWTP)
Engine type	
Electrical output	900 kWe
Thermal output	1100 kW
Commissioning	

The Seikai Teisyo Project is located in mainland China. JFE Engineering Corporation is installing Waukesha CHP package at a new wastewater treatment plant. The customers needed to maximize heat production for the treatment process which made the APG1000 the optimum decision.





### technical features

feature Factory built CHP package	description Oil and water circuits optimized for maximum thermal efficiency	advantages  -Hot water return temperature of up to 80°C (176°F) suitable for many applications -Wide range of customer side flow rates are permissible			
Electric jacket water pump and temperature control valve	Engine side coolant circuit flow is controlled by genset mounted pump	-Fast engine warm-up is possible -Post shutdown cooling is possible			
ECP8000E genset control panel included	Full featured CHP control panel is provided with simple hook-up to genset mounted junction box	-Customer configurable spare I/O is provided to control ancillary equipment -Connect to genset with a simple Ethernet cable -Monitor the CHP system remotely			

### technical data


Engine	Waukesha 16V150LTD, Four Cycle, Lean Burn
Cylinders	V16
Piston displacement	48 L (2924 cu. in.)
Bore & stroke	152 × 165 mm (5.98" × 6.5")
Jacket water system capacit	y 240 L (63 gal.)
LT water capacity	20 L (5 gal.)
HT water capacity	132 L (35 gal.)
Lube oil capacity	485 L (128 gal.)
Starting system	24VDC Electric
Dry weight	13,730 kg (30,200 lb.)

#### Dimensions I x w x h mm (inch)

CHP Package 7165 (282) × 1926 (76) × 2263 (89)

### Weights kg (lb)

CHP Package 14900 (32800)



## performance data

### Natural gas

	Cooling system	ooling system 1,800 rpm/60 Hz				1,500 rpm/50 Hz					
NOx	configuration	Pel (kW)	ηel (%)	Pth (kW)	ηth (%)	ηtot (%)	Pel (kW)	ηel (%)	Pth (kW)	ηth (%)	ηtot (%)
"TA Luft NOx 1.0 g/bhp.hr"	Standard	1,100	41.7	1,053	39.9	81.6	1,000	42.1	905	38.0	80.1
	CHP	1,100	41.7	1,260	47.7	89.4	1,000	42.1	1,067	44.9	87.0
"1/2 TA Luft NOx 0.5 g/bhp.hr"	Standard	_	_	-	_	_	1,000	40.8	976	39.9	80.7
	CHP	_	_	_	_	_	1,000	40.8	1,132	46.3	87.1
0.6 g/bhp.hr	Standard	1,100	40.8	1,095	40.6	81.4	_	_	_	_	_
	CHP	1,100	40.8	1,300	48.3	89.1	_	_	_	_	_
Biogas											
"TA Luft NOx 1.0 g/bhp.hr"	Standard	1,100	40.9	995	37.0	77.9	1,000	42.0	835	35.0	77.0
	CHP	1,100	40.9	1,192	44.3	85.2	1,000	42.0	1,005	42.1	84.1



GE Power & Water 1101 West Saint Paul Ave. Waukesha, WI 53188-4999 P: 1.262.547.3311

F: 1.262.549.2759

Visit us online at: www.ge-waukesha.com

©2011, 2013 General Electric Company All Rights Reserved