









CATERPILLAR®

LOW OIL PRESSURE



EMERGENCY STOP



HIGH WATER TEMP



ENGINE OVERSPEED



OVERCRANK



SPARE 1


SPARE 2

SPARE 3

FAULT SHUTDOWN



FAULT



ENGINE

LAMP

ALARM

SERVICE



MC **AUTOMATIC BATTERY CHARGER**
RATED FOR CONTINUOUS DUTY

MODEL NO. **MBC6TC-24V-10A-L3C/NC**

MCS P/N **B612-418-23** S/N **1047**

CATERPILLER P/N **7C3874** (Optional)

REG. PART NO. **509 000-30** Options

REFER TO INSTRUCTION MANUAL FOR DETAILS
ALARM MODULE FAILURE CONTACT SETTING
(WHEN PROVIDED) 10A. AT 120 V.A.C. OR 25 D.C.

INPUT **95-130/190-260 V. 50/60HZ. 1 PH. 27.5A.**
(BRANCH CIRCUIT PROTECTION REQUIRED)

OUTPUT **24 NOM. V.D.C. 10 AMPS**

BATTERY **L3C/RC TYPE 12/20 CELLS**

1.275/± SP. GR., MAX. CAP. 230 AH

LAKE BLUFF, ILL. U.S.A. P/N 3854001 401 804-1

4AMP 3AG
SLO-BLO

DC POS

30A 3AG
SLO-BLO